

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) An information display system, comprising:
 - an information processing apparatus;
 - an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and
 - a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,
 - an imaging device that images a range-representation of less than an entire portion of an image on the display surface containing the position at which the pointing apparatus is to point on the display image at an imaging point of time, and outputs imaged image information corresponding to the range-representation,
 - the information processing apparatus including, a pointing coordinate specification device to accept the imaged image information from the pointing apparatus, decide which part of display image information corresponding to the display image at an imaging point of time the imaged image information corresponds to, and specify coordinates of the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision,
 - a display image information storage device to store the display image information therein, and
 - a display image information generation device to composite ~~and display~~ a pointer cursor to and at the specified pointing coordinates on the display image information.

2. (Currently Amended) An information display system, comprising:

- an information processing apparatus;
- an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and
- a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,
 - an imaging device that images a range representation of less than an entire portion of an image on the display surface containing the position at which the pointing apparatus is to point on the display image at an imaging point of time, and outputs imaged image information corresponding to the range representation,
 - a pointing coordinate specification device to accept the imaged image information from the imaging device, decide which part of the display image information corresponding to the display image that the imaged image information at the imaging point of time corresponds to, and specify coordinates of the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision,
 - the information processing apparatus including a display image information storage device to store the display image information therein, and
 - a display image information generation device to composite ~~and display a~~ pointer cursor to and at the specified pointing coordinates on the display image information.

3. (Currently Amended) An information display system, comprising:

- an information processing apparatus;
- an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and
- a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,

an imaging device that images a ~~range~~representation of less than an entire portion of an image on the display surface containing the position at which the pointing apparatus is to point on the display image at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~representation, and

the information processing apparatus including a pointing coordinate specification device to accept the imaged image information from the pointing apparatus, decide which part of display image information corresponding to the display image at an imaging point of time the imaged image information corresponds to, and specify coordinates of the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision,

a display image information storage device to store therein the display image information corresponding to the display image, and

a display image information generation device to generate the image information stored in the display image information storage device, as the display image information, and composite ~~and display~~ a pointer cursor to and at the pointing coordinates on the display image information as specified by the pointing coordinate specification device.

4. (Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface;

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,

an imaging device that images a ~~range~~representation of less than an entire portion of an image on the display surface containing the position at which the pointing

apparatus is to point on the display image at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~representation,

a pointing coordinate specification device to accept the imaged image information from the imaging device, decide which part of the display image information corresponding to the display image that the imaged image information at the imaging point of time corresponds to, and specify coordinates of the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision,

the information processing apparatus including a display image information storage device to store therein the display image information corresponding to the display image, and

a display image information generation device to generate the image information stored in the display image information storage device, as the display image information, and composite ~~and display~~ a pointer cursor to and at the pointing coordinates on the display image information as specified by the pointing coordinate specification device.

5. (Currently Amended) The information display system as defined in claim 1, further comprising:

the ~~range-representation~~ to be imaged being a ~~an~~ imagable range-representation which is set by a collimation device included in the imaging device, and the central part of the imagable range-representation set by the collimation device being the position at which the pointing apparatus is to point, the coordinates of the position being acquired as the pointing coordinates.

6. (Original) The information display system as defined in claim 1, further comprising:

the decision on which part of the display image information corresponding to the display image at the imaging point of time the imaged image information corresponds to,

being rendered by generating template image information from the imaged image information, and then performing pattern matching between the template image information and the display image information corresponding to the display image at the imaging point of time.

7. (Original) The information display system as defined in claim 1, the pointing apparatus being a portable information equipment which has an imaging function and a communication function.

8. (Withdrawn) The information display system as defined in claim 1, further comprising:

the pointing apparatus including a command input device, the information processing apparatus including a command processing device to accept and process a command from the pointing apparatus, and that, in the information processing apparatus, when the command is given from the command input device after the specification of the pointing coordinates, the command process being performed so as to reflect a result of the process on the pointing coordinates.

9. (Original) An information processing apparatus for use in the information display system as defined in claim 1, comprising:

functions of accepting the imaged image information outputted from the pointing apparatus, deciding which part of the display image information corresponding to the display image at the imaging point of time the imaged image information corresponds to, specifying the position at which the pointing apparatus is to point, as the pointing coordinates from the result of the decision, and thereafter compositing and displaying the pointer cursor to and at the specified pointing coordinates on the display image information.

10. (Original) A pointing apparatus for use in the information display system as defined in claim 2, comprising:

functions of deciding which part of the display image information corresponding to the display image at the imaging point of time the imaged image information by the imaging device corresponds to, and specifying the coordinates of the position at which the pointing apparatus is to point, as the pointing coordinates from the result of the decision.

11. (Currently Amended) ~~A data processing program for the information processing apparatus, in which data processing to be performed by the information processing apparatus as defined in claim 9 comprises:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the information processing apparatus according to claim 9 comprising:

~~accepting an instruction for causing a computer executing the instruction to~~
accept the imaged image information outputted from the pointing apparatus, and deciding which part of the display image information corresponding to the display image at the imaging point of time the imaged image information corresponds to, and

specifying the position at which the pointing apparatus is to point, as the pointing coordinates from the result of the decision, and thereafter compositing and displaying the pointer cursor to and at the specified pointing coordinates on the display image information.

12. (Currently Amended) ~~A data processing program for the pointing apparatus, in which data processing steps to be performed by the pointing apparatus as defined in claim 10 comprises:~~ A computer program product comprising a CPU-useable medium having a

CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the pointing apparatus according to claim 10 comprising:

deciding an instruction for causing a computer executing the instruction to decide which part of the display image information corresponding to the display image at the imaging point of time the imaged image information from the imaging device corresponds to, and

specifying the coordinates of the position at which the pointing apparatus is to point, as the pointing coordinates from the result of the decision.

13. (Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, comprising:

the pointing apparatus images a range-representation of less than an entire portion of an image on the display surface containing the position at which it is to point on the display image at an imaging point of time, by an imaging device included in the pointing apparatus, and outputs imaged image information corresponding to the range-representation, onto the information processing apparatus, and

the information processing apparatus side accepts the imaged image information and the pointing coordinate motion vector from the pointing apparatus, decides which part of the display image information corresponding to the display image that the imaged image information at the imaging point of time corresponds to, specifies the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision, and thereafter composites and displays a pointer cursor to and at the specified pointing coordinates on the display image information.

14. (Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, comprising:

the pointing apparatus images a ~~range~~representation of less than an entire portion of an image on the display surface containing the position at which it is to point on the display image at an imaging point of time, by an imaging device included in the pointing apparatus, obtains imaged image information corresponding to the ~~range~~representation, decides which part of the display image information corresponding to the display image that the imaged image information at the imaging point of time corresponds to, specifies the position at which the pointing apparatus is to point, as pointing coordinates from a result of the decision, and outputs pointing coordinate information for the specified pointing coordinates, to the information processing apparatus side, and

the information processing apparatus side composites and displays a pointer cursor to and at the pointing coordinate corresponding to the pointing coordinate information delivered from the pointing apparatus.

15. (Currently Amended) The pointer cursor display method in the information display system as defined in claim 13, further comprising:

the ~~range~~representation to be imaged being a ~~an~~ imagable range-representation which is set by a collimation device included in the imaging device, and the central part of the imagable range-representation set by the collimation device being the position at which the pointing apparatus is to point, coordinates of the position being acquired as the pointing coordinates.

16. (Original) The pointer cursor display method in the information display system as defined in claim 13, further comprising:

the decision on which part of the display image information corresponding to the display image at the imaging point of time the imaged image information corresponds to being rendered by generating template image information from the imaged image information, and then performing pattern matching between the template image information and the display image information corresponding to the display image at the imaging point of time.

17. (Withdrawn-Currently Amended) An information display system, comprising:
an information processing apparatus;
an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,

an imaging device that images ~~an arbitrary range~~ a representation of less than an entire portion of an image on the display surface which is to be imaged by the pointing apparatus at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~ representation, and

a pointing coordinate motion vector calculation device that compares the imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle based on the imaging device, and then calculates a pointing coordinate motion vector from a result of the comparison; and

the information processing apparatus includes a display image information storage device to store therein display image information corresponding to the display image, and

a display image information generation device to composite a pointer cursor displayed on the display image information at the current point of time, to the display image information, and then ~~display outputs~~ the pointer cursor at the position which is distant, in correspondence with the pointing coordinate motion vector calculated by the pointing apparatus to the information display apparatus.

18. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, the pointing apparatus including,

an imaging device that images a ~~certain arbitrary range~~ representation of less than an entire portion of an image on the display surface at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~ representation, and

the information processing apparatus includes a pointing coordinate motion vector calculation device to compare the imaged image information at a current point of time as obtained from the imaging device of the pointing apparatus and imaged image information temporally preceding the current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of the imaging device of the pointing apparatus, and then calculate a pointing coordinate motion vector from a result of the comparison,

a display image information storage device to store therein display image information corresponding to the display image, and

a display image information generation device to composite a pointer cursor displayed on the display image information at the current point of time, to the display image information, and then display outputs the pointer cursor at the position which is distant, in correspondence with the pointing coordinate motion vector calculated by the pointing apparatus to the information display apparatus.

19. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus; the pointing apparatus including an imaging device that images an arbitrary range a representation of less than an entire portion of an image on the display surface which is to be imaged by the pointing apparatus at an imaging point of time, and outputs imaged image information corresponding to the range representation,

an imaged image information storage device to store therein imaged image information temporally preceding a current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle based on the imaging device, and

a pointing coordinate motion vector calculation device to compare the imaged image information at the current point of time and the imaged image information stored in the imaged image information storage device, and then calculate a pointing coordinate motion vector from a result of the comparison; and

the information processing apparatus includes a display image information storage device to store therein display image information corresponding to the display image, and

a display image information generation device to generate the image information stored in the display image information storage device, as the display image information, and composite a pointer cursor displayed on the display image information at the current point of time, to the display image information, and then ~~display-outputs~~ the pointer cursor at the position which is distant, in correspondence with the pointing coordinate motion vector calculated by the pointing apparatus to the information display apparatus.

20. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus; the pointing apparatus including an imaging device that images a ~~certain arbitrary range~~ representation of less than an entire portion of an image on the display surface at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~ representation; and

the information processing apparatus includes an imaged image information storage device to store therein imaged image information temporally preceding a current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of the imaging device of the pointing apparatus,

a pointing coordinate motion vector calculation device to compare the imaged image information at the current point of time as obtained from the imaging device of the

pointing apparatus and the imaged image information stored in the imaged image information storage device, and then calculate a pointing coordinate motion vector from a result of the comparison,

a display image information storage device to store therein display image information corresponding to the display image, and

a display image information generation device to generate the image information stored in the display image information storage device, as the display image information, and composite a pointer cursor displayed on the display image information at the current point of time, to the display image information, and then ~~display-outputs~~ the pointer cursor at the position which is distant, in correspondence with the pointing coordinate motion vector calculated by the pointing apparatus to the information display apparatus.

21. (Withdrawn) The information display system as defined in claim 17, further comprising:

in that the process to compare the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time and then calculating the pointing coordinate motion vector from the result of the comparison performs pattern matching between template image information generated from the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, thereby to decide which part of the imaged image information temporally preceding the current point of time the imaged image information at the current point of time corresponds to, whereupon it finds a movement magnitude and a moving direction of the imaged image information at the current point of time, on the basis of a result of the decision, so as to calculate the pointing coordinate motion vector from the found movement magnitude and moving direction.

22. (Withdrawn) The information display system as defined in claim 17, the pointing apparatus being a portable information equipment which has an imaging function and a communication function.

23. (Withdrawn) The information display system as defined in claim 17, further comprising:

the pointing apparatus including a command input device, the information processing apparatus including a command processing device to accept and process a command from the pointing apparatus, and that, in the information processing apparatus, when the command is given from the command input device after specification of pointing coordinates, the command process is performed so as to reflect a result of the process on the pointing coordinates.

24. (Withdrawn) The pointing apparatus for use in the information display system as defined in claim 17, further comprising:

functions of comparing the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the arbitrary range is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device, and then calculating the pointing coordinate motion vector from the result of the comparison, so as to output the pointing coordinate motion vector to the information processing apparatus.

25. (Withdrawn) An information processing apparatus for use in the an information display system as defined in claim 18, further comprising:

functions of comparing the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the imaging is performed the plurality of times, by or without,

changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, calculating the pointing coordinate motion vector from the result of the comparison, and compositing the pointer cursor displayed on the display image at the current point of time, to the display image information, and then displaying the pointer cursor at the position which is distant in correspondence with the calculated pointing coordinate motion vector.

26. (Withdrawn-Currently Amended) ~~A data processing program for a pointing apparatus, in which data processing to be performed by the pointing apparatus as defined in claim 24 comprises:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the information processing apparatus according to claim 24 comprising:

an instruction for causing a computer executing the instruction to comparing
compare the imaged image information at the current point of time and the imaged image
 information temporally preceding the current point of time, as are obtained in such a way that
 the ~~arbitrary range~~ representation is imaged the plurality of times, by or without, changing at
 least one of the imaging position and the imaging angle, by the imaging device included in the
 pointing apparatus, and then calculating the pointing coordinate motion vector from the result
 of the comparison; and

the outputting the pointing coordinate motion vector to the information
 processing apparatus.

27. (Withdrawn) ~~A data processing program for an information processing apparatus, in which data processing to be performed by the information processing apparatus as defined in claim 25 comprises:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed

on a CPU causes the CPU to be performed by the information processing apparatus according to claim 25 comprising:

an instruction for causing a computer executing the instruction to compare
~~comparing~~ the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the imaging is performed the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, and then calculating the pointing coordinate motion vector from the result of the comparison; and

the compositing the pointer cursor displayed on the display image at the current point of time, to the display image information, and then displaying the pointer cursor at the position which is distant in correspondence with the calculated pointing coordinate motion vector.

28. (Withdrawn-Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image at an imaging point of time displayed by the information display apparatus, comprising:

the pointing apparatus compares imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as are obtained in such a way that ~~an arbitrary range~~ a representation is imaged a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of an imaging device included in the pointing apparatus, by the imaging device, whereupon a

pointing coordinate motion vector is calculated from a result of the comparison, so as to output the pointing coordinate motion vector to the information processing apparatus; and the information processing apparatus composites a pointer cursor displayed on the display image at the current point of time, to the display image information, and displays the pointer cursor at the position which is distant in correspondence with the pointing coordinate motion vector calculated by the pointing apparatus.

29. (Withdrawn-Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed at an imaging point of time by the information display apparatus, comprising:

the pointing apparatus images ~~an arbitrary range~~ a representation by an imaging device included in the pointing apparatus; and

that the information processing apparatus side compares imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as are obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of the imaging device included in the pointing apparatus, calculates a pointing coordinate motion vector from a result of the comparison, and composites a pointer cursor displayed on the display image at the current point of time, to the display image information, and displays the pointer cursor at the position which is distant in correspondence with the calculated pointing coordinate motion vector.

30. (Withdrawn) The pointer cursor display method in the information display system as defined in claim 28, further comprising:

the process to compare the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time and then calculate the pointing coordinate motion vector from the result of the comparison, performs pattern matching between template image information generated from the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, thereby to decide which part of the imaged image information temporally preceding the current point of time the imaged image information at the current point of time corresponds to, whereupon it finds a movement magnitude and a moving direction of the imaged image information at the current point of time, on the basis of a result of the decision, so as to calculate the pointing coordinate motion vector from the found movement magnitude and moving direction.

31. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus; the pointing apparatus including an imaging device that images ~~an arbitrary range~~ a representation of less than an entire portion of an image on the display surface which is to be imaged by the pointing apparatus at an imaging point of time, and outputting imaged image information corresponding to the ~~range~~ representation, and

a pointing coordinate motion vector calculation device that compares the imaged image information at a current point of time and imaged image information

temporally preceding the current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle based on the imaging device, and then calculating a pointing coordinate motion vector from a result of the comparison; and

the information processing apparatus includes a display image information storage device to store therein display image information corresponding to the display image,

a pointing coordinate specification device to find a tentative pointing position of a pointer cursor after being moved, on the basis of the display image information, the imaged image information from the pointing apparatus, and the pointing coordinate motion vector, and specifying a pointing position of the pointer cursor after being moved, as pointing coordinates within ~~a range~~the representation containing the tentative pointing position, and

a display image information generation device to composite ~~and display the~~ pointer cursor to and at the specified pointing coordinates on the display image information.

32. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus; the pointing apparatus including an imaging device capable of imaging ~~an arbitrary range~~a representation of less than an entire portion of an image on the display surface which is to be imaged by the pointing apparatus at an imaging point of time, and outputting imaged image information corresponding to the ~~range~~representation; and

the information processing apparatus includes a pointing coordinate motion vector calculation device to compare the imaged image information at a current point of time

and imaged image information temporally preceding the current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle attained by the imaging device of the pointing apparatus, and then calculating a pointing coordinate motion vector from a result of the comparison,

a display image information storage device to store therein display image information corresponding to the display image,

a pointing coordinate specification device to find a tentative pointing position of a pointer cursor after being moved, on the basis of the display image information, the calculated pointing coordinate motion vector, and the imaged image information from the pointing apparatus, and specify a pointing position of the pointer cursor after being moved, as pointing coordinates within a ~~range~~the representation containing the tentative pointing position, and

a display image information generation device to composite ~~and display~~ the pointer cursor to and at the specified pointing coordinates on the display image information.

33. (Withdrawn-Currently Amended) An information display system, comprising:

an information processing apparatus;

an information display apparatus which displays display image information held in the information processing apparatus, on a display surface; and

a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus; the pointing apparatus including an imaging device that images ~~an arbitrary range~~a representation of less than an entire portion of an image on the display surface which is to be imaged by the pointing apparatus at an imaging point of time, and outputs imaged image information corresponding to the ~~range~~representation,

a pointing coordinate motion vector calculation device that compares the imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle based on the imaging device, and then calculating a pointing coordinate motion vector from a result of the comparison, and

a pointing coordinate specification device to find a tentative pointing position of a pointer cursor after being moved, on the basis of the imaged image information, the pointing coordinate motion vector, and the display image information, and then specifying a pointing position of the pointer cursor after being moved, as pointing coordinates within a ~~range~~the representation containing the tentative pointing position; and

the information processing apparatus includes a display image information storage device to store therein display image information corresponding to the display image, and

a display image information generation device to composite ~~and display~~ the pointer cursor to and at the specified pointing coordinates on the display image information.

34. (Withdrawn-Currently Amended) The information display system as defined in claim 31, further comprising:

the pointing coordinate specification process, which is performed by the pointing coordinate specification device, sets the ~~range~~representation with reference to the tentative pointing position, computes correlations at respective positions by performing pattern matching between the imaged image and the display image information at the imaging point of time within the set ~~range~~representation, and specifies the pointing coordinates after the motion, on the basis of the computed correlations.

35. (Withdrawn-Currently Amended) An information processing apparatus for use in the information display system as defined in claim 31, further comprising:

functions of finding the tentative pointing position of the pointer cursor after being moved, on the basis of the display image information stored in the display image information storage device, the imaged image information from the pointing apparatus, and the pointing coordinate motion vector, specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the ~~range~~representation containing the tentative pointing position, and compositing and displaying the pointer cursor to and at the specified pointing coordinates.

36. (Withdrawn-Currently Amended) The pointing apparatus for use in an information display system as defined in claim 31, further comprising:

functions of comparing the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary-range~~representation is imaged the plurality of times by or without, changing at least one of the imaging position and the imaging angle, of the imaging device included in the pointing apparatus, by the imaging device, and then calculating the pointing coordinate motion vector from the result of the comparison, so as to output the pointing coordinate motion vector to the information processing apparatus.

37. (Withdrawn-Currently Amended) An information processing apparatus for use in the information display system as defined in claim 32, further comprising:

functions of comparing the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary-range~~representation is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device, calculating the

pointing coordinate motion vector from the result of the comparison, finding the tentative pointing position of the pointer cursor after being moved, on the basis of the calculated coordinate motion vector, the imaged image information, and the display image information, specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the range representation containing the tentative pointing position, and compositing and displaying the pointer cursor to and at the specified pointing coordinates.

38. (Withdrawn-Currently Amended) A pointing apparatus for use in the information display system as defined in claim 33, further comprising:

functions of comparing the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary range~~ range representation is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device calculating the pointing coordinate motion vector from the result of the comparison, finding the tentative pointing position of the pointer cursor after being moved, on the basis of the pointing coordinate motion vector, the imaged image information at the imaging point of time, and the display image information, and specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the range representation containing the tentative pointing position.

39. (Withdrawn-Currently Amended) ~~A data processing program of an information processing apparatus, in which data processing to be performed by the information processing apparatus as defined in claim 35, comprises:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the information processing apparatus according to claim 35 comprising:

~~an instruction for causing a computer executing the instruction to find~~
~~finding~~ the tentative pointing position of the pointer cursor after being moved, on the basis of the display image information stored in the display image information storage device, the imaged image information from the pointing apparatus, and the pointing coordinate motion vector;

the specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the ~~range~~representation containing the tentative pointing position; and

compositing and displaying the pointer cursor to and at the specified pointing coordinates.

40. (Withdrawn-Currently Amended) ~~A data processing program of a pointing apparatus, in which data processing to be performed by the pointing apparatus as defined in claim 36 comprises:~~A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the information processing apparatus according to claim 36 comprising:

an instruction for causing a computer executing the instruction to ~~comparing~~
compare the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary range~~representation is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device and then calculating the pointing coordinate motion vector from the result of the comparison; and

outputting the pointing coordinate motion vector to the information processing apparatus.

41. (Withdrawn-Currently Amended) ~~A data processing program of an information processing apparatus, in which data processing to be performed by the information processing apparatus as defined in claim 37:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed on a CPU causes the CPU to be performed by the information processing apparatus according to claim 37 comprising:

an instruction for causing a computer executing the instruction to compare
~~comparing the imaged image information at the current point of time and the~~
 imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary range~~representation is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device, and then calculating the pointing coordinate motion vector from the result of the comparison;

finding the tentative pointing position of the pointer cursor after being moved, on the basis of the calculated coordinate motion vector, the imaged image information, and the display image information,

specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the ~~range~~representation containing the tentative pointing position; and

compositing and displaying the pointer cursor to and at the specified pointing coordinates.

42. (Withdrawn-Currently Amended) ~~A data processing program of a pointing apparatus, in which data processing steps to be performed by the pointing apparatus as defined in claim 38, comprises:~~ A computer program product comprising a CPU-useable medium having a CPU-readable program, wherein the CPU-readable program when executed

on a CPU causes the CPU to be performed by the information processing apparatus according to claim 38 comprising:

an instruction for causing a computer executing the instruction to compare
~~comparing~~ the imaged image information at the current point of time and the imaged image information temporally preceding the current point of time, as are obtained in such a way that the ~~arbitrary range~~ representation is imaged the plurality of times, by or without, changing at least one of the imaging position and the imaging angle of the imaging device included in the pointing apparatus, by the imaging device, and then calculating the pointing coordinate motion vector from the result of the comparison;

finding the tentative pointing position of the pointer cursor after being moved, on the basis of the pointing coordinate motion vector, the imaged image information at the imaging point of time, and the display image information; and

specifying the pointing position of the pointer cursor after being moved, as the pointing coordinates within the ~~range~~ representation containing the tentative pointing position.

43. (Withdrawn-Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, comprising:

the pointing apparatus compares imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as are obtained in such a way that ~~an arbitrary range~~ a representation is imaged a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of an imaging device included in the pointing apparatus, by the imaging device, a pointing

coordinate motion vector is calculated from a result of the comparison, so as to output the pointing coordinate motion vector to the information processing apparatus; and

the information processing apparatus finds a tentative pointing position of a pointer cursor after being moved, on the basis of the imaged image information from the pointing apparatus, the pointing coordinate motion vector, and the display image information, specifies a pointing position of the pointer cursor after being moved, as pointing coordinates within ~~a range~~ the representation containing the tentative pointing position, and composites and displays the pointer cursor to and at the specified pointing coordinates on the display image information corresponding to the display image.

44. (Withdrawn-Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, comprising:

the pointing apparatus images ~~an arbitrary range~~ a representation by an imaging device included in the pointing apparatus; and

the information processing apparatus compares imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as are obtained by imaging a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of the imaging device included in the pointing apparatus, by the imaging device, calculates a pointing coordinate motion vector from a result of the comparison, finds a tentative pointing position of a pointer cursor after being moved, on the basis of the calculated coordinate motion vector, the imaged image information, and the display image information corresponding to the display image, specifies a pointing

position of the pointer cursor after being moved, as pointing coordinates within ~~a range~~the representation containing the tentative pointing position, and composites and displays the pointer cursor to and at the specified pointing coordinates on the display image information.

45. (Withdrawn-Currently Amended) A pointer cursor display method in an information display system having an information processing apparatus, an information display apparatus which displays display image information held in the information processing apparatus, on a display surface, and a pointing apparatus which points at an arbitrary position on a display image displayed by the information display apparatus, comprising:

the pointing apparatus compares imaged image information at a current point of time and imaged image information temporally preceding the current point of time, as are obtained by imaging ~~an arbitrary range~~a representation a plurality of times, by or without, changing at least one of an imaging position and an imaging angle of an imaging device included in the pointing apparatus, by the imaging device, calculates a pointing coordinate motion vector from a result of the comparison, that it finds a tentative pointing position of a pointer cursor after being moved, on the basis of the pointing coordinate motion vector, and the display image information corresponding to the display image, and specifies a pointing position of the pointer cursor after being moved, as pointing coordinates within ~~a range~~the representation containing the tentative pointing position; and

the information processing apparatus composites and displays the pointer cursor to and at the specified pointing coordinates on the display image information.

46. (Withdrawn-Currently Amended) The pointer cursor display method in the information display system as defined in claim 43, further comprising:

the pointing coordinate specification process sets the ~~range~~representation with reference to the tentative pointing position, computes correlations at respective positions by

performing pattern matching between the imaged image and the display image information at the imaging point of time within the set ~~range~~representation, and specifies the pointing coordinates after the motion, on the basis of the computed correlations.